

XN5548 & XN5548-P

Single Phase Off-Grid Solar Inverter



Efficient Higher Revenue

- Built-in 110A MPPT solar charge
- Wide PV input voltage range



Intelligent Simple O&M

- Over load / over temperature / short circuit protection
- Smart battery charger design, optimize battery performance



Flexible Abundant Configuration

- Support grid / generator input
- Compatible with lithium battery
- Up to 6 units in parallel (P model)
- Multiple charging voltage levels for different batteries
- Multiple work mode, support AC priority, solar priority

	XN5548	XN5548-P
Rated Power	5500VA/5500W	
Input		
Voltage	230Vac	
Selectable Voltage Range	170Vac~280Vac (for personal computers) 90Vac~280Vac (for home appliances)	
Frequency Range	50Hz / 60Hz (auto sensing)	
Output		
AC Voltage Regulation (Batt. Mode)	230Vac±5%	
Surge Power	11000VA	
Overload Capability	5s@ ≥ 150% load; 10s@110%~150% load	
Efficiency (Peak)	94%	
Transfer Time	10ms (for personal computers); 20ms (for home appliances)	
Waveform	Pure Sine Wave	
Battery		
Battery Nominal Voltage	48Vdc	
Floating Charge Voltage	52Vdc	
Overcharge Protection	62Vdc	
Solar Charger & AC Charge		
Solar Charger Type	MPPT	
Maximum PV Array Power	6000W	
MPPT Range	120Vdc~450Vdc	
Maximum PV Array Open Circuit Voltage	500Vdc	
Maximum Utility Charge Current	80A	
Maximum Solar Charge Current	110A	
Protection		
Protection	AC Short Circuit Protection, AC Over Current Protection, Over Temperature Protection, etc.	
Communication		
Display	LCD	
Communication Port	RS232 / RS485	
Standard Compliance		
Safety / EMC	CE	
General Data		
Dimension (W x H x D)	297 x 472 x 133 mm	
Net Weight	10.5kg	
Protect Degree	IP21	
Operating Temperature	0° C ~ +55° C	
Storage Temperature	-15° C ~ +60° C	
Humidity	5%~95% (non-condensing)	
Parallel	No	Up to 6 pcs